

ELP Flex Printer



Three configurations with interchangeable print heads

203dpi • 300dpi • 600dpi



Standard Interfaces

- USB 2.0
- Ethernet
- Parallel
- 9-pin RS-232
- USB host for scanner or keyboard

Stand Alone Printing

Stand Alone Mode promotes cost savings by ease of use, freeing up valuable floor space and allowing diverse printer placement. No PC needed.



Head Office. Etek Technology Centre, Dow Road, Prestwick Aerospace Park, Monkton, Prestwick KA9 2TU

T. +44(0)1292 834 000
E. Sales@etek-europe.com
W. etek-europe.com



Highlights

- Interchangeable printheads
- 1 printer = 3 printers (203-300-600dpi)
- Exceptional print registration
- ZPL Emulation - Best in the industry
- Large color LCD touch screen
- Minimal waste during calibration
- Easy loading and removal of labels/ribbons
- Direct-gear driven - no belts to wear out
- Stand alone printing mode.
- No PC needed. Very user friendly operation

Features

- Standard 600 meter ribbon lengths
- Up to 14" per second print speed
- Holds 8" OD media rolls
- Standard 1" core ribbons, CSO/CSI
- 2 year printer warranty
- Optional Cutter

ELP™ Flex Printer

Interchangeable Print Heads



Labels for Life.

■ Standard □ Option

LABEL PRINTER

Printhead	Print method	Thermal transfer / Direct thermal		
	Print resolution dpi	203	300	600
	Print speed up to mm/s	356	254	102
	Print width mm	104	104	104
Material	Media roll total diameter up to mm	208	208	208
	Label width mm	25.4-116*	25.4-116*	25.4-116*
	Label length up to mm	25,400	11,430	2,540
Ribbon	Ribbon Ink coated (1" cores)	CSO/CSI	CSO/CSI	CSO/CSI
	Ribbon length variable up to m	600	600	600
	Ribbon width up to mm	114	114	114
Print Alignment	Media is left (L) or center (C) justified	L	L	L
Dual Side Printing	Print on both sides of media	NO	NO	NO
Printer Dimensions	Width x Height x depth mm	270x308x515	270x308x515	270x308x515
	Weight (lbs.)	33	33	33
Electronics	Processor high speed clock rate MHz	32-bit RISC	32-bit RISC	32-bit RISC
	RAM MB	128	128	128
	Memory IFFS MB Flash	128	128	128
	ZPL emulation	YES	YES	YES
	Stand-Alone Printing	YES	YES	YES
	Slot for Compact Flash Memory Card	■	■	■
	Slot for wireless LAN card	RS-232	RS-232	RS-232
	Warning signal	Acoustic signal in case of error		
Interfaces	Centronics bi-directional acc. IEEE 1284	■	■	■
	RS-232 (9 pin)	■	■	■
	USB 2.0 High Speed for PC	■	■	■
	Ethernet 10/100 Base T	■	■	■
	USB host for scanner or keyboard	■	■	■
	Bluetooth	□	□	□
	WLAN card 802.11 b/g	□	□	□
Options	Cutter	□	□	□
	Peel-off kit	□	□	□

¹⁾ All materials are approximate values. Small labels, very thin, narrow, thick or stiff materials as well as labels with strong adhesives need to be tested first.



Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 7/7/2017.