

### ◆ PCO2-14™ Polyimide Curing Oven

A clean process oven designed for polyimide baking and curing applications

The Despatch PCO2-14™ electrically heated oven was designed to meet the specific process requirements for hard baking polyimide coatings in an inert atmosphere. This high-performance, clean process oven (ISO Class 5/Class 100 recirculated airflow) offers many unique components, including a pressure relief system, an oxygen control system and a process monitoring system which allows the oven to achieve the strict oxygen level and atmospheric requirements involved in polyimide curing.

**Pressure Relief System:** In the “hard bake” polyimide cure process, residual solvent is removed and desired surface properties are finalized. The process of removing solvents requires that the oven contain equipment to help prevent and collect solvent condensation. Despatch designed the PCO2-14™ with a pressure relief system that includes a removable “cold trap”, an easy-to-clean condensate trap that helps to prevent polyimide buildup in the oven’s exhaust.

#### **Oxygen Monitor and Control System:**

The PCO2-14™ is an inert atmosphere oven which allows the oxygen level to be maintained at 20ppm or less to help prevent oxidation of the polyimides being cured. The oven contains an O2 monitor which is wired to the purge valve and turns the nitrogen purge on whenever the oxygen level is above the O2 monitor set point. Once the nitrogen purge is complete, the O2 level is maintained at a set point by a controller that operates a modulating valve during the curing process. This process minimizes the nitrogen usage and allows for consistent and repeatable product curing.



#### **Process Monitoring System:**

The oven’s PC features Protocol 3™ software to allow for communication between the PC and the oven, an Ethernet connection and a 15” (38.1cm) flat panel display screen. The Protocol 3™ software communicates directly with the oven’s Protocol 3™ controller, O2 controller, O2 monitor and integrated PC to observe and data log entire cycles and provide the user with real-time information on set points, actual chamber temperatures and O2 levels throughout the entire process.



## PC02-14

### PHYSICAL SPECIFICATIONS

Chamber size (width x depth x height) *Clear opening width is reduced by 1.5 in. (3.8 cm) due to 3/4 in. (1.9 cm) shelf supports on each side.	25.5* x 26 x 37 in. 64* x 66 x 94 cm
Capacity in cubic feet (liters)	14 (396)
Overall size (width x depth x height)	58 x 51 x 74 in. 147 x 129.5 x 188 cm
Electrical: Three phase 60 HZ, 208 volts	Heater: 16 kW
Electrical: Three phase 60 HZ, 240 volts	Heater: 16 kW
Electrical: Three phase 50 HZ, 380 volts	Heater: 16 kW
Electrical: Three phase 50 HZ, 415 volts	Heater: 16 kW
Electrical: Three phase 60 HZ, 480 volts	Heater: 16 kW
Ventilation exhaust diameter	3 in. (7.6cm) flange connection
Number of shelves provided	2 stainless steel
Maximum number of shelves	11 on 3" (7.62 cm) centers
Shelf dimensions (width x depth)	25 x 25.75 in. (63.8 x 65.4 cm)
Approximate net weight	1000 lbs. (455 kg)
Approximate domestic shipping weight (export adds weight)	1200 lbs. (545 kg)

### FUNCTIONAL SPECIFICATIONS

Time to temperature with no load (50°C to 100°C)	3 minutes (non-ISO Class 5)
Time to temperature with no load (50°C to 200°C)	9 minutes (non-ISO Class 5)
Time to temperature with no load (50°C to 260°C)	15 minutes (non-ISO Class 5)
Time to temperature with no load (50°C to 350°C)	35 minutes (non-ISO Class 5)
Cooling time to temperature with no load (100°C to 65°C) *Based on cooling water supplied at 3 GPM (11.4 lpm), 13 °C	15 minutes*
Cooling time to temperature with no load (175°C to 65°C) *Based on cooling water supplied at 3 GPM (11.4 lpm), 13 °C	20 minutes*
Cooling time to temperature with no load (260°C to 65°C) *Based on cooling water supplied at 3 GPM (11.4 lpm), 13 °C	25 minutes*
Cooling time to temperature with no load (350°C to 65°C) *Based on cooling water supplied at 3 GPM (11.4 lpm), 13 °C	30 minutes*
Temperature uniformity at 100°C	+/- 1°C
Temperature uniformity at 200°C	+/- 2°C
Temperature uniformity at 260°C	+/- 3°C
Temperature uniformity at 350°C	+/- 3.5°C
Control stability	+/- 0.5°C
Operating range with 20°C ambient temperature	35°C-350°C (95°F-662°F)
Maximum load capacity	400 lbs (181 kg)
Maximum shelf capacity	50 lbs (23 kg)
1.5 HP recirculating fan with horizontal airflow	950 CFM (448 liter/sec)

Notes: Uniformity figures are based on a nine-point test conducted in an empty oven after stabilization period. Uniformity can vary slightly depending on unit and operating conditions. Minimum operating temperature and cooling times are based on 20°C ambient temperature measured at the fresh air inlet. Times to temperature with no load are based on non-ISO Class 5 (non-Class 100) conditions. Class 100 HEPA filtration will limit ramp rates to 5°C per minute. Specifications are subject to change without notice. If the existing specifications differ from yours, ask about our customizing capabilities.

### FEATURES AT A GLANCE

- ◆ Compact cabinet design that minimizes footprint
- ◆ All interior seams continuously welded on insulation side to protect the work chamber from contamination
- ◆ 4" (10.2cm) thick insulation in chamber to minimize heat loss, air leakage and external thermal spots
- ◆ Recirculation air is 100% filtered through a 99.99% HEPA filter for ISO Class 5 (Class 100) or better operation
- ◆ Magnehelic gauge monitors HEPA filter pressure to indicate when to replace filter
- ◆ Protocol 3TM control with large LCD display, integrated data logging capabilities and USB port for simple oven set-up and data export.
- ◆ Silicone-free construction
- ◆ End of cycle, high-limit audible and visual alarms
- ◆ Programmable, electronic door lock
- ◆ Installation and burn-off of HEPA filter including post-burn off cleaning of the chamber
- ◆ Cleaning and triple bagging in clean room before shipment
- ◆ Port 1" (2.5cm) with tri-clamp fitting in center rear of oven



- ◆ The removable "cold trap" is an easy-to-clean condensate trap that prevents polyimide buildup in the oven's exhaust.
- ◆ Optional CE Compliance

**Warning: Despatch PC02-14™ ovens are not to be used with flammable solvents, materials or enclosed containers. Soft bake of the polyimide coatings must be done in a Class A oven prior to hard baking in the PC02-14™.**

### SERVICE AND TECHNICAL SUPPORT

service phone: 1-800-737-8110  
service international: 1-573-317-3054

dpsupport@itwae.com  
parts@itwae.com

### GLOBAL HEADQUARTERS

main phone: 1-800-726-0110  
international/main: 1-952-469-5424  
sales: 1-800-726-0550  
international/sales: 1-952-469-8240  
sales@despatch.com

### WWW.DESPATCH.COM

8860 207th Street West  
Minneapolis, MN 55044 USA

**Despatch**  
Thermal Processing Technology **ITW EAE**